

# T3

## Portable Gas Detection Equipment



# T3

## Four gas personal monitor

**When lives and property are at risk and you need gas detection equipment that is totally reliable, you need Crowcon. For over 40 years Crowcon has been developing and manufacturing high quality products with a reputation for reliability and technical innovation.**

**Crowcon provide both single gas and multigas monitors for personal monitoring and portable safety applications providing protection against a wide range of industrial gas hazards. The T3 offers you compliance, robustness and a low cost of ownership in a simple to use solution.**



### Choosing the portable gas detector for your needs

**Single button operation, small size and clear top-mounted display make the T3 a favourite in the market amongst those working in today's most arduous industrial environments.**

Designed with the user in mind, the top mount display, full function data and event logs, audible, visual and vibrating alarms deliver top end performance in a small and lightweight package. Gases include the most common four (carbon monoxide, methane, oxygen and hydrogen sulphide), but also an expanded range: ammonia, ozone, sulphur dioxide, hydrogen filtered carbon monoxide (for steel plants) and IR carbon dioxide (for safe area use only).

#### Robust

Rugged impact resistant design provides extra shock and vibration protection	Provides protection in the harshest environments
Water and Dust resistant to IP65 and IP67	
Can be submerged in water	

#### Effective Warning

95 dB audible alarm	Ensures prompt evacuation from hazard zone
Vivid red/blue visual alarm	
Vibrating alarm	

#### Reliable

Proven sensor technology and software operation	Covers you over an extended shift
Clear calibration-due warning	
Lithium-ion battery provides over 14 hours continuous operation from a single charge with no memory effects	

#### User friendly

Single button operation for all functions	Can be operated with gloved hands
Top mounted, backlit display of all gas readings, diagnostics and battery life	'At a glance' operating status

**Please see the back page for full technical specifications.**

# T3 Gas Tester



With an increased focus on regular bump testing of gas detection instruments both through regulation and individual company requirements, bump testing has become even more important to ensure safety for users.

The T3 Gas Tester offers a solution that ensures compliance. By checking the sensors respond to a known concentration of gas and utilising the T3 instrument's internal functionality, it makes it a cost-effective, fast and simple solution.

Bump testing exposes each sensor to a known concentration of gas to confirm that it responds correctly and to ensure that the unit is working correctly. If it is found not to be working, then the T3 Gas Tester flags the need for the instrument to be re-calibrated or serviced.

The T3 Gas Tester allows bump testing of T3 instruments fitted with flammable, oxygen, carbon monoxide, hydrogen sulphide and carbon dioxide sensors. The tester can bump all four gases in the instrument within 60 seconds. Using a fixed flow regulator reduces the cost of testing, allowing approximately 140 bumps per 34L cylinder of quad gas.

## Fast and simple to use

Automatic detector recognition	Test indicated automatically
Automatic gas delivery	Confident the correct gas volume has been delivered

## Reliable

Rugged and robust	Durability for harsh environments
Maintenance free	Low cost of ownership

## Flexible

Wall, desk and DIN rail mountable	User configurable
Suitable for in-field and on-site gas testing	
Stand alone unit	
Fast and simple to use	

## Part Ordering Information:

<b>GT-T3-01 T3</b>	Gas Tester Kit 1 (includes tester and 1m inlet tubing)
<b>GT-T3-02 T3</b>	Gas Tester Kit 2 (as Kit 1 plus fixed flow regulator)
<b>GT-T3-03 T3</b>	Gas Tester Kit 3 (as Kit 2 plus gas cylinder holder)

<b>REG01</b>	Fixed flow regulator (0.5 l/min)
<b>AC0510</b>	Gas cylinder holder
<b>C03289</b>	1m inlet tubing

### T3 Product Specification:

<b>Size</b>		114 x 71 x 48mm (tapers to 20mm) (4.5 x 2.8 x 1.9ins)
<b>Weight</b>		295g (10.4oz)
<b>Alarms</b>	Audible	95dB multiple alarm sounds allow selection of distinctive tones for different alarm levels
	Vibrating	Internal vibrating alarm
<b>Display</b>		Graphic LCD with backlight, giving simultaneous display for all gas channels. Graphic symbols for battery (with proportional indication of remaining operation time), healthy operation or fault warning. Start up indication when calibration is due, overdue, or service required
<b>Display mode</b>	Normal display	Real time gas concentration levels
	Display recall	Peak readings and TWA
<b>Data logging</b>	Timed datalogging	50 hours at 1-minute data rate (>12,000 data logs of 4 channels)
	Threshold logging	Starts after adjustable preset level
	Event logging	>5,000 events
<b>Battery</b>		Rechargeable Li-ion battery
<b>Operating time</b>		Based on four gas unit with flammable sensor: A 5 hour charge from flat provides at least 10 hours of continuous use. A 12 hour charge provides at least 14 hours of continuous use
<b>Sampling</b>		Diffusion or hand aspirator
<b>Operating temp range*</b>		-20°C to +55°C (-4°F to +131°F)
<b>Humidity</b>		20-90% RH @ 40°C non-condensing
<b>Ingress protection</b>		IP65 and IP67
<b>Approval codes</b>	Europe	ATEX II 2 G Ex ia d IIC T4 Gb (-20°C ≤ Ta ≤ +55°C) BASEEFA05ATEX0187
	International	IECEx Ex ia d IIC T4 Gb (-20°C ≤ Ta ≤ +55°C)BAS05.0059
	North America	CSA Class I Division 1 Groups A, B, C and D
<b>Safety standards</b>	Europe	EN60079-0, EN60079-11, EN60079-1, 94/9/EC
	North America	CSA22.2, 152
	Operating standards	EN50270, EN50271, EN50104, EN45544, EN60079, IEC61508
<b>PC interface</b>		RS232 connection from interface module in charger RS232/USB converter available
<b>Calibration</b>		Can be routinely calibrated using Portables PC software or Crowcon Checkbox IMH
<b>Accessories</b>		Integral alligator clip
<b>Optional accessories</b>		Universal harness plate, shoulder strap, chest harness, aspirator assembly (flow plate, bulb and 2m/6ft tubing), fixed and telescopic sample probes, and an in-line water trap
<b>Charging options</b>		Single way drop-in charger with UK, EU or US plug or in-line 110V/220V supply Single way drop-in charger with options as above including PC interface 5 way multi-charger with universal power supply Vehicle adapter for in-vehicle charging Universal charger for vehicle, wall and desk mounting with a multi-region plug (supplied with EU/UK/US/Australian inserts) and status indication

\*Toxic and oxygen sensors are not rated for continuous operation at high temperatures. Consult Crowcon if operating temperatures are likely to exceed 40°C (104°F) for extended periods

### T3 Gas Tester Specification:

<b>Size</b>	125 x 185 x 80mm (4.9 x 7.3 x 3.1ins)
<b>Weight</b>	250g (8.8oz)
<b>Instrument supported</b>	T3
<b>Gases supported</b>	Flammable, CO, O <sub>2</sub> , H <sub>2</sub> S and CO <sub>2</sub>
<b>Test time</b>	Typically 30 seconds
<b>Tests performed</b>	Sensor response to gas Visual alarm Audible alarm General pass/ fail indication
<b>Automatic gas delivery</b>	0.5 litres/minute (l/min)
<b>Gas inlet/ exhaust</b>	1/1
<b>Accessories</b>	Tubing, gas cylinder holder, fixed flow regulator

### Gases and ranges

Ranges and alarms vary by country and application, these can be configured as required. Each channel can have two instantaneous alarms. Toxic channels also have TWA alarms. Flammable gas calibration is available for methane, propane, butane, pentane, hydrogen and ethylene as standard.

Gas	Range	Typical Alarm (UK)
<b>Flammable</b>	0- 100% LEL	20%
<b>Oxygen (O<sub>2</sub>)</b>	0-25%	19/23.5%
<b>Hydrogen sulphide (H<sub>2</sub>S)</b>	0-100ppm	5ppm
<b>Carbon monoxide (CO)</b>	1-500ppm	30ppm
<b>Sulphur dioxide (SO<sub>2</sub>)</b>	0-20ppm	1ppm
<b>Ozone (O<sub>3</sub>)</b>	0-1ppm	0.1ppm
<b>Ammonia (NH<sub>3</sub>)</b>	0-100ppm	25ppm
<b>**Carbon dioxide (CO<sub>2</sub>)</b>	0-5%	0.5ppm

\*\* T3 is available in a safe area CO<sub>2</sub> version offering 0-5% carbon dioxide measurement. The CO<sub>2</sub> sensor replaces the flammable option and can be supplied with oxygen and toxic sensors.

Crowcon reserves the right to change the design or specification of the product without notice. Check [www.crowcon.com](http://www.crowcon.com) for updates.

[www.crowcon.com](http://www.crowcon.com)

**UK:**  
Tel: +44 (0) 1235 557700  
Fax: +44 (0) 1235 557718  
Email: [sales@crowcon.com](mailto:sales@crowcon.com)

**US:**  
Tel: +1 859 957 1039  
Toll Free: 800 527 6926  
Fax: +1 513 957 1044  
Email: [salesusa@crowcon.us](mailto:salesusa@crowcon.us)

**NL:**  
Tel: +31 10 421 1232  
Fax: +31 10 421 0542  
Email: [eu@crowcon.com](mailto:eu@crowcon.com)

**SG:**  
Tel: +65 6745 2936  
Fax: +65 6745 0467  
Email: [sales@crowcon.com.sg](mailto:sales@crowcon.com.sg)

**CN:**  
Tel: +86 (0) 10 6787 0335  
Fax: +86 (0) 10 6787 4879  
Email: [saleschina@crowcon.com](mailto:saleschina@crowcon.com)

**IN:**  
Tel: +91 22 6708 0400  
Fax: +91 22 6708 0405  
Email: [salesindia@crowcon.com](mailto:salesindia@crowcon.com)

 **CROWCON**  
Detecting Gas Saving Lives